

-C-S-E==2021== -C-O-M-FU-T-E-R==-O-R-G-A-N-I-Z-A-T-I-O-N

Ŧ						C	<u> </u> _ 1.0	E 12	5-5 U-	Ē	 S ☆ L L A R	E N Y T U T U T	もと保の文精	シは第二次部方	R E A M W O	の 文積なフ ト	一般市住地町・	一保の文精なフ
THUTTURU 3	A M S O M L M Z M	4+ ac as co	ト社明 をに美と 字印 び	▶ 10号=10	2 8 8 4 V 10 49	HS YHE MA	日本 日本の日間 三字の 日本		EO ANAGENT	の一文精なフィト社明、をに			なフト社開をに美と学印	audeeuoooge Se		社明 をに美と 学印 び技す	ZONMACHUTEL	ト 社会 をに美と 字印 び技士
	0 A N	H 03 (- II	田田 ふば	Han A 1	60 PH			1 1		美と 字印		5 Y 3			ېد ب	√[-5]∿	1	

DR



From Last Time...

Define the following terms:

- Instruction Set Architecture (ISA)
- Compiler
- Assembler

Measuring Performance

Agenda:

- Performance Definition
- Performance Metrics: CPU Execution Time and Throughput
- Benchmarks: SPEC 2006
- Alternative Performance Metrics: MIPS and FLOPS
 Patterson:
 - Today Sections 1.4 1.10.
 - Wednesday Sections 2.1 2.7.

Analogy with Commercial Airplanes

What does it mean do say that one computer or airplane is better than another?

Airplane	Passenger Capacity	Cruising range (miles)	Cruising speed (mph)	Passenger throughput (passengers × mph)
Boeing 777	375	4630	610	$375 \times 610 = 228,750$
Boeing 747	470	4150	610	$470 \times 610 = 286,700$
Airbus A3xx	656	8400	600	656 × 600 = 393,600
Concorde	132	4000	1350	$132 \times 1350 = 178,200$
Douglas DC-8-50	146	8720	544	$146 \times 544 = 79,424$

To know which of the four planes exhibits the best performance, we need to define a criteria for measuring "performance".

<u>Performance Criteria:</u>	Winner:
Speed	Concorde
Capacity	Boeing 747
Range	Douglas DC-8-50
Throughput	Airbus A3xx
~ .	-W-2-M-

Computer Performance

- Performance of a computer is based on the following criteria:
 - 1. Execution Time: Elapsed time between the start and the end of one task
 - 2. Throughput: Total number of tasks finished in a given interval of time.
 - An IT manager will be interested in having a higher overall throughput while a computer user will like to have a lower execution time for his task.
 - Using execution time as the criteria, the performance of a machine *X* is defined as

$$Performance_{x} = \frac{1}{Execution \ time_{x}}$$

Performance ratio (*n*) between two machines *X* and *Y* is defined as

$$n = \frac{Performance_x}{Performance_y} = \frac{Execution \quad time_y}{Execution \quad time_x}$$

Computer Performance (2)

Activity 1: If machine X runs a program in 30 seconds and machine Y runs the same program in 45 seconds, how much faster is X than Y?

<u>Activity 2:</u> Discuss which of the following two options is better suited to enhance performance from a user's perspective:

(a) Upgrading a machine to a faster CPU

(b) Adding additional processors to the machine so that multiple processors are used for different tasks.

Repeat for an IT manager?

What is Execution Time?



Command time in Unix can be used to determine the elapsed time and CPU time for a particular program

Syntax:time <name_of_program>Result:1.180u0.130s

CPU user time CPU system time

 $\underbrace{0:0:44.95}_{\text{Elapsed time in h:m:s}}$

2.9% ... CPU time/Elapsed time

CPU Performance

Performance based on User CPU time is called the CPU performance

$$CPU \ Performance_{x} = \frac{1}{CPU \ Execution \ time_{x}}$$

Performance based on System time is called the system performance

System Performance_x =
$$\frac{1}{System Execution time_x}$$

Vendors specify the speed of a computer in terms of clock cycle time or clock rate. For example, a 1GHz Pentium is generally faster than a 500MHz Pentium all other factors being the same. We define the clock cycles formally next.

Multiples defined:

$$1K = 2^{10} \approx 10^{3} \text{ (kilo)}$$

$$1M = 2^{20} \approx 10^{6} \text{ (mega)}$$

$$1G = 2^{30} \approx 10^{9} \text{ (giga)}$$

$$1T = 2^{40} \approx 10^{12} \text{ (tera)}$$

$$1P = 2^{50} \approx 10^{15} \text{ (peta)}$$

Clock



- All events in a computer are synchronized to the clock signal
- Clock signal is therefore received by every HW component in a computer
- Clock cycle time: is defined as the duration of 1 cycle of the clock signal
- Clock cycle rate: is the inverse of the clock cycle time.
- CPU execution time is therefore defined as

$$\begin{vmatrix} CPU & Execution & time \\ Program & x \end{vmatrix} = \begin{vmatrix} CPU & Clock & cycles \\ Program & x \end{vmatrix} \times Clock & Cycle & Time \\ = \frac{CPU & Clock & Cycles & Program & x}{Clock & Rate}$$

Clock (2)

Timing Programs generally return the average number of clock cycle needed per instruction (denoted by CPI) $[CPU \ Execution \ time] = CPU \ Clock \ Cycles \ Program \ x$ Program x Clock Rate Instruction Count Program $x \times CPI$ Clock Rate <u>Activity 3:</u> For a CPU, instructions from a high-level language are classified in 3 classes **Instruction Class** B A **(**) CPI for the instruction class 1 2 3 Two SW implementations with the following instruction counts are being considered Instruction counts per instruction class А B Implementation 1 2 Implementation 2 4

Which implementation executes the higher number of instructions? Which runs faster? What is the CPI count for each implementation? $-W^2-M$

Performance Comparison

To compare performance between two computers,

- 1. Select a set of programs that represent the workload
- 2. Run these programs on each computer
- 3. Compare the average execution time of each computer

Activity 4: Based on the average (arithmetic mean) execution time, which of the two computer is faster?

Execution Time	Computer A	Computer B
Program 1	2	10
Program 2	100	105
Program 3	1000	100
Program 4	25	75

Performance Comparison: Benchmarks

- Benchmarks: are standard programs chosen to compare performance between different computers.
- Benchmarks are generally chosen from the applications that a user would typically use the computer to execute.
- Benchmarks can be classified in three categories:
 - 1. Real applications reflecting the expected workload, e.g., multimedia, computer visualization, database, or macromedia director applications
 - 2. Small benchmarks are specialized code segments with a mixture of different types of instructions
 - 3. Benchmark suites containing a standard set of real programs and applications. A commonly used suite is SPEC (System Performance Evaluation Corporation www.spec.org) with different versions available, e.g., SPEC'89, SPEC'92, SPEC'95, SPEChpc96, and SPEC CPU2006 suites.

Performance Comparison: SPEC Suite (2)

- SPEC'95 suite has a total of 18 programs (integer and floating point) which are called benchmarks. However, SPEC CPU2006 has a total of 29 programs – integer and floating point operations
- SPEC ratio for a program is defined as the ratio of the execution time of the program on a Sun UltraSPARC II (296 MHz processor) to the execution time on the measured machine.
- CINT2006 is the geometric mean of the SPEC ratios obtained from the integer programs. The geometric mean is defined as $CINT2000 = \sqrt[n]{\prod_{i=1}^{n} (SPEC \ ratio)_i}$

CFP2000 is the geometric mean of the SPEC ratios from the floating-point programs
 Activity 5: Complete the following table to predict the performance of machines A and B

	Time on A	Time on B	Normali	zed to A	Normalized to B		
	(seconds)	(seconds)	Α	В	Α	В	
Program 1	5	25					
Program 2	125	25					
Arithmetic Mean							
Geometric Mean							
		-W-2M-				13	

Performance Comparison: SPEC'95 Benchmark

Benchmark	Description
go	Artificial intelligence; plays the game of Go
m88ksim	Motorola 88k chip simulator; runs test program
gcc	The Gnu C compiler generating SPARC code
compress	Compresses and decompresses file in memory
li	Lisp interpreter
ijpeg	Graphic compression and decompression
perl	Manipulates strings and prime numbers in the special-purpose programming language Perl
vortex	A database program
tomcatv	A mesh generation program
swim	Shallow water model with 513 x 513 grid
su2cor	quantum physics; Monte Carlo simulation
hydro2d	Astrophysics; Hydrodynamic Naiver Stokes equations
mgrid	Multigrid solver in 3-D potential field
applu	Parabolic/elliptic partial differential equations
trub3d	Simulates isotropic, homogeneous turbulence in a cube
apsi	Solves problems regarding temperature, wind velocity, and distribution of pollutant
fpppp	Quantum chemistry
wave5	Plasma physics; electromagnetic particle simulation

Performance Comparison: SPEC CPU2006 Benchmarks

Q11. What source code is provided? What exactly makes up these suites?

CINT2006 and CFP2006 are based on compute-intensive applications provided as source code. CINT2006 contains 12 benchmarks: 9 use C, and 3 use C++. The benchmarks are:

С	PERL Programming Language
С	Compression
С	C Compiler
С	Combinatorial Optimization
С	Artificial Intelligence: go
С	Search Gene Sequence
С	Artificial Intelligence: chess
С	Physics: Quantum Computing
С	Video Compression
C++	Discrete Event Simulation
C++	Path-finding Algorithms
C++	XML Processing
	C C C C C C C C C C C C C C C C C C C

		-
416.gamess	Fortran	Quantum Chemistry
433.milc	С	Physics: Quantum Chromodynamics
434.zeusmp	Fortran	Physics/CFD
435.gromacs	C/Fortran	Biochemistry/Molecular Dynamics
436.cactusADM	C/Fortran	Physics/General Relativity
437.leslie3d	Fortran	Fluid Dynamics
444.namd	C++	Biology/Molecular Dynamics
447.dealII	C++	Finite Element Analysis
450.soplex	C++	Linear Programming, Optimization
453.povray	C++	Image Ray-tracing
454.calculix	C/Fortran	Structural Mechanics
459.GemsFDTD	Fortran	Computational Electromagnetics
465.tonto	Fortran	Quantum Chemistry
470.lbm	С	Fluid Dynamics
481.wrf	C/Fortran	Weather Prediction
482.sphinx3	С	Speech recognition

Fortran Fluid Dynamics

CFP2006 has 17 benchmarks: 4 use C++, 3 use C, 6 use Fortran, and 4 use a mixture of C and Fortran. The benchmarks are:

410.bwaves

Improving Performance

 $\begin{vmatrix} CPU & Execution & time \\ Program & x \end{vmatrix} = \frac{CPU & Clock & Cycles & Program & x \\ Clock & Rate \end{vmatrix}$

Performance of a CPU can be improved by:

- 1. Increasing the clock rate (decreasing the clock cycle time)
- 2. Enhancements in the Compiler to decrease the instruction count in a program
- 3. Improvement in the CPU to decrease the clock cycle per instruction (CPI)

Unfortunately factors (1 - 3) are not independent. For example, if you increase the clock frequency then the CPI may also increase.

Performance: Don'ts

- 1. Do not expect performance of one aspect of a machine to improve overall performance by an amount proportional to the size of improvement (Law of diminishing returns, Amdahl's Law).
- 2. Do not use MIPS (million instructions per second) as a performance metric

$$MIPS = \frac{Instruction Count in a program}{Execution time \times 10^{6}}$$

- a. Does not take into account capability of the instruction set computers with different ISA will have different instructions for a given task.
- b. MIPS will be different for the same machine depending on the program

MIPS =
$$\frac{\text{Instruction Count in a program}}{\text{Execution time} \times 10^6}$$

= $\frac{\text{Instruction Count}}{\text{Clock Rate} \times 10^6}$ = $\frac{\text{Clock Rate}}{\text{CPI} \times 10^6}$

Performance: Don'ts

<u>Activity 6:</u> For a CPU, instructions from a high-level language are classified in 3 classes

Instruction Class	А	В	С
CPI for the instruction class	1	2	3

Two SW implementations with the following instruction counts are being considered

	Instructi for ea	on counts (in bach instruction	oillions) class
	А	В	С
Implementation 1	5	1	1
Implementation 2	10	1	1

Assuming that the clock rate is 500 MHz, calculate the (a) MIPS and (b) execution time.

Performance: Don'ts

- 5. Do not use synthetic benchmarks (vendor created) to predict performance
 - Commonly used synthetic benchmarks are Whetstone and Dhrystone
 - Whetstone was based on Algol in an engineering environment and later converted to Fortran
 - Dhrystone was written in Ada for systems programming environments and later converted to C
 - Such synthetic benchmarks do not reflect the applications typically run by a user
- 5. Do not use the arithmetic mean of execution time to predict performance. Geometric means provide better estimates.

Exercise

The following table shows results for the SPEC2006 benchmark programs on an AMD Barcelona.

Benchmark name	Instr. Count (billions)	Execution time (seconds)	Reference time (seconds)
Perl	2118	500	9770
mcf	336	1200	9120

Calculate: (a) CPI if the clock cycle time is 0.333 ns (b) SPECratio

(c) Geometric mean of the SPECratio